



Product name:
EHT Power Supply

Product code:
CIVIL-MES-124-0029



Description

EHT Power Supply

Technical specification

The switching transformer is specially wound so that the output maintains a stable voltage with time, as opposed to most other commercial where the voltage will drop with time. An auxiliary output is provided to drive cathode heaters etc. The adjustable 5KV output is fully isolated and the output is monitored by a digital display. Output current is electronically limited to 2mA and the outputs are also current limited by 100K resistors to avoid larger transient currents. In addition to the 0-5KV outputs, there are further outputs linked by 25M Ω resistors. power supply suitable for driving tubes and electrostatic experiments. Continuously variable, 0-2.5KV or 0-5KV at a maximum current of 2mA. Two secondary outputs with 25M Ω resistors (total 50M for 5KV range). Auxiliary output, 6.3V a.c. at 1A, protected by resettable fuse. Bright 12.5mm green LED display indicating output. This provides outputs appropriate for electrostatic experiments with a short circuit current of 60 μ A. An Independent earth terminal is available for earthing of any one of the five output sockets. Sockets suitable for standard 4mm plugs or shrouded plugs. Specifications: Mains supply: 230V 5% , 50Hz Fuse: 315mA (L) Output: 0 to 5KV DC, 2mA or 2.5KV DC, 2 mA Input: 220V-240V, 50/60 Hz Height including handle is 187mm Secondary outputs with 25M Ω safety resistors. Auxiliary output of 6.3V AC, 1A for cathode heaters, protected by resettable fuse Independent Earth Terminal for earthing of any one of the five output sockets.



Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exports India

Email us at: export@civilmechanicalindia.com