NAUGRA®

Product name:	Product code:
Heavy Duty Lathe 3000 mm Between Centres	CMI-NP-0880



Description

A rigid cast iron centre lathe with 660 mm swing over bed and 3000 mm between centres, used for turning, facing, boring, threading and taper work in workshops and training institutes.

Technical specification

Spindle speeds	16 to 1000 rpm in 12 steps
Bed width	400 mm
Main motor	10 HP (7.5 kW), 3 phase, 415 V AC 50 Hz
Metric threads	0.5 to 7 mm pitch
Tailstock taper	MT4
Construction	Cast iron bed and headstock

Standard Accessories

- Faceplate
- Three jaw chuck
- Dead centres
- Tool post spanner set

Heavy Duty Lathe 3000 mm Between Centres is built on a hardened and ground bed with a geared headstock for dependable cutting. It suits engineering colleges, ITIs and production workshops for practical machining training and light production jobs.

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Features

- Hardened and precision ground bed ways
- Geared headstock with multiple spindle speeds
- Lead screw and feed rod for threading and feeds
- Quick change gear box for inch and metric threads
- Induction hardened bed and wide carriage for long shaft turning
- Emergency stop and chuck guard for safe operation

Technical Specifications

Swing over bed	660 mm
Distance between centres	3000 mm
Spindle bore	52 mm