NAUGRA®

Product name:	Product code:
Gap Bed Centre Lathe 1250 mm	CMI-NP-0884



Description

A rigid cast iron centre lathe with 400 mm swing over bed and 1250 mm between centres, used for turning, facing, boring, threading and taper work in workshops and training institutes.

Technical specification

Bed width	250 mm
Main motor	5 HP (3.7 kW), 3 phase, 415 V AC 50 Hz
Metric threads	0.5 to 7 mm pitch
Tailstock taper	MT4
Construction	Cast iron bed and headstock

Standard Accessories

- Faceplate
- Three jaw chuck
- Dead centres
- Tool post spanner set

Gap Bed Centre Lathe 1250 mm is built on a hardened and ground bed with a geared headstock for dependable cutting. It suits engineering colleges, ITIs and production workshops for practical machining training and light production jobs.

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Features

- Hardened and ground bed ways
- Geared headstock with multiple spindle speeds
- Lead screw and feed rod for threading and feeds
- Quick change gear box for inch and metric threads
- Removable gap piece to accommodate larger diameter jobs
- Emergency stop and chuck guard for safe operation

Technical Specifications

Swing over bed	400 mm
Distance between centres	1250 mm
Spindle bore	40 mm
Spindle speeds	35 to 1600 rpm in 12 steps