NAUGRA®

Product name:	Product code:
Geared Head Centre Lathe 1500 mm	CMI-NP-0885



Description

A rigid cast iron centre lathe with 350 mm swing over bed and 1500 mm between centres, used for turning, facing, boring, threading and taper work in workshops and training institutes.

Technical specification

Spindle speeds	40 to 2000 rpm in 12 steps
Bed width	250 mm
Main motor	5 HP (3.7 kW), 3 phase, 415 V AC 50 Hz
Metric threads	0.5 to 7 mm pitch
Tailstock taper	MT3
Construction	Cast iron bed and headstock

Standard Accessories

- Faceplate
- Three jaw chuck
- Dead centres
- Tool post spanner set

Geared Head Centre Lathe 1500 mm is built on a hardened and ground bed with a geared headstock for dependable cutting. It suits engineering colleges, ITIs and production workshops for practical machining training and light production jobs.

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Features

- Hardened and precision ground bed ways
- Geared headstock with multiple spindle speeds
- Lead screw and feed rod for threading and feeds
- Quick change gear box for inch and metric threads
- Gear driven headstock with lever speed selection
- Emergency stop and chuck guard for safe operation

Technical Specifications

Swing over bed	350 mm
Distance between centres	1500 mm
Spindle bore	40 mm