Product name:	Product code:
Benchtop pH and Conductivity Meter with ATC Probe	CMI-IND-0041



Description

Microprocessor benchtop pH and conductivity meter with automatic temperature compensation and multi-point calibration for process water, effluent and chemical samples. Used in industrial QC and environmental labs.

Technical specification

Temperature range	0 to 100 deg C
Display	Backlit LCD
Power supply	230 V AC adaptor, 50 Hz

Standard Accessories

- pH electrode
- Conductivity cell
- Buffer solutions 4, 7, 9.2

The meter measures pH, mV, conductivity and TDS using a combination electrode and a conductivity cell with built-in temperature sensors. Multi-point calibration with automatic buffer recognition keeps readings accurate. It is intended for routine analysis in plants and labs.

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Features

- pH range 0 to 14 with 0.01 resolution
- Conductivity 0 to 200 mS/cm
- ATC temperature compensation 0 to 100 deg C
- Up to 5 point calibration
- Data logging and RS232/USB port

Technical Specifications

pH range	-2.00 to 16.00 pH
pH accuracy	+/- 0.01 pH
Conductivity range	0 to 200 mS/cm
Conductivity accuracy	+/- 0.5 percent of reading