NAUGRA®

Product name:	Product code:
Road Marking Wet Film Thickness Comb Gauge Set	CMI-IND-0058



Description

Stainless steel notched comb gauges and a thermoplastic layer thickness gauge for checking wet film and applied thickness of road marking paint. Used by contractors and highway inspectors during line marking.

Technical specification

Material	Stainless steel 304
Standards	ASTM D4414, ISO 2808 Method 1A, EN 1824 (field practice)
Pieces	3 comb gauges and 1 depth gauge

Standard Accessories

- Cleaning cloth
- Carry case
- Spare depth gauge pin

The comb gauge is pressed onto freshly applied paint and the highest notch wetted shows the film thickness in microns, while a hook-type gauge checks hot-applied thermoplastic depth in mm. Correct thickness is essential for marking durability and retroreflectivity. The set is light, rugged and meant for roadside use.

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Features

- Four-sided stainless steel comb gauges
- Ranges 50 to 2000 microns
- Thermoplastic depth gauge 0 to 10 mm
- Laser-etched notches for easy reading
- Rugged carry case

Technical Specifications

Comb gauge ranges	50-800, 100-1000 and 500-2000 um
Notch steps	25 to 100 um
Thermoplastic gauge range	0 to 10 mm
Thermoplastic gauge resolution	0.1 mm