Product name:	Product code:
Faucet Hydrostatic Pressure and Leak Test Bench	CMI-IND-0555

Description

Hydraulic test bench that applies water pressure up to 25 bar to taps, mixers and valves to check body strength and seat leak tightness. Used by bath fittings makers for 100 percent and sample testing.

Technical specification

- Adapters
- Pressure gauge
- Hose set

The faucet is clamped to a fixture and pressurised with water at a set value for the specified time. Leakage from the body, spout or valve seat is seen by the operator. The bench handles open and closed position tests with quick-change adapters.

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Features

- Hydraulic pump for up to 25 bar
- Digital pressure gauge with hold timer
- Quick fit adapters for 1/2 and 3/4 inch connections
- Drain tray and transparent guard
- Open and closed valve test options

Technical Specifications

Test standards	IS 8931, EN 817 pressure tests
Test pressure	0 to 25 bar
Pressure accuracy	+/-0.5 percent FS
Hold time	0 to 999 s
Connections	1/2 inch BSP, 3/4 inch BSP
Pump	High pressure piston, 0.75 kW
Frame	SS 304 bench with tray
Power supply	230 V AC, 50 Hz

Standard Accessories