Product name:	Product code:
conductivity meter	ELE-0004



Description

conductivity meter

Technical specification

CELL CONSTANT	Adjustable.
SENSOR	Conductivity Cell.
POWER	230V Â± 50 Hz AC.

DIGITAL CONDUCTIVITY METER

DISPLAY	3.5 Digit LED.
RANGE	5 Ranges, 0 to 1000Mhos / cm.
ACCURACY	Â± 1% of F.S. Â± 1 Digit.
TEMPERATURE COMP.	Manual 0 To 50 deg. C
CELL CONSTANT	Adjustable.
SENSOR	Conductivity Cell.
POWER	230V Â± 50 Hz AC.

MICROPROCESSOR CONDUCTIVITY / TDS / TEMP.

DISPLAY	16 X 2 Alpha Numeric LCD Display
RANGE	0.1 Î¼S to 200mS (6 Decadic Ranges)
RESOLUTION	0.01 Î¼S.
ACCURACY	Â± 1% of F.S.Â± 1 Digit
CALIBRATION	Auto / Manual.
TEMPERATURE COMP.	0 to 100 UC.
CELL CONSTANT	0.1 To 5.0 Adjustable.
SENSOR	Up to 100 Samples.
POWER	230V Â± 50 Hz. AC.

DELUXE DIGITAL CONDUCTIVITY METER

DISPLAY	3.5 Digit LED.
RANGE	5 Ranges, 0 to 1000Mhos / cm.
ACCURACY	Â± 1% of F.S. Â± 1 Digit.
TEMPERATURE COMP.	Auto / Manual 0 To 50 deg. C

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com