Product name:	Product code:
Digital-TDS meter	ELE-0005



Description

Digital-TDS meter

Technical specification

0.1 Conductivity Cell	0.09 To .11 Cell Constant
1 Conductivity Cell	0.9 To 1.1 Cell Constant
TDS Factor	0.20 To 1.00
Conductivity Tempco Range	0 To 3.0 % Per Â°c
Cond. Compentation	
Temperature Range	0 To 55 Â°c
Power Requirement	230 Volt + Or 10 %,50 Hz
Display	2 Â½ Digit Digital Panel Meter

SPECIFICATIONS

Range

Conductivity	2Ã¬s To 200mS With 0.1 `Cell Constant And 20Ã¬s To 200mS With Unity Cell Constant in 5 Decade Range
TDS	2 PPM To 2 PPT With 0.1 Cell Constant And 20 PPM To 200 PPT With Unity Cell Constant, in 5 Decade Range
Temperature	0 Â°c To 100Â°c

Resolution

Conductivity	0.01 In Lowest Range With 0.1 Cell Constant
TDS	0.01 Ppm With 0.1 Cell Constant;
Temperature	1 Â°c.

Accuracy

Conductivity / TDS	+ 1 % Of F.s. + 1 Count.
Temperature	+ 1 Â°c.

Cell Compensation

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com