Product name:	Product code:
Wood Working Mortiser – Tenoning Machine	SEL-0031

Description

Wood Working Mortiser – Tenoning Machine

Technical specification

Vertical Adjustment Bottom Block 0 mm - 60 mm
Vertical Adjustment Scribing Head 95 mm
Vertical Adjustment Top Block 0 mm - 100 mm

Tenoner has two separately powered heads which enable both sides of the tenon to be cut in one pass, the shoulders being offset if required. The heads are each equipped with 4 replaceable shear-cutting knives, two spur cutters for clean shouldered tenons, a mechanical digital readout on the head and are powered by two 2.2kW Motors. An additional third 4kW motor is provided to drive a scribing head for accurately scribing individual mouldings. A scribing head is an optional extra.

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Diameter of Tooling Bottom Block 175 mm
Diameter of Tooling Scribing Head 210 mm
Diameter of Tooling Top Block 175 mm
Dust Extraction Outlet 150 mm
Horizontal Adjustment Scribing Head 30 mm
Horizontal Adjustment Top Block ±32 mm
Length of Shaft 75 mm
Main Cutter Heads 2 @ 175 mm x 60 mm
Max Length of Tenon Single Pass 155 mm
Max Length of Tenon Two Passes 205 mm
Model TESH
Nett Weight 470 kg
Overall L x W x H 1,320 mm x 1,020 mm x 1,560 mm
Rating Industrial
Scribing Head Shaft Diameter 30 mm
Table Size 800 mm x 310 mm
Timber Cap' Height Fence @ 45 130 mm
Timber Cap' Width Fence @ 45 195 mm
Timber Cap' Width Fence @ 90 310 mm