Product name:	Product code:
Facsimile Dynamic Demonstrator	Consumer0010

Description

Facsimile Dynamic Demonstrator

Technical specification

Facsimile Dynamic Demonstrator

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

- Type: Desktop Transceiver
- Applicable Line: Public Switched Telephone Network
- Compatibility: CCITT Group 3
- Scan Method: Horizontal -Contact Image Sensor, Vertical-intermittent Scanning by stepper Motor
- Document Size: Max – 216 X 1 000 mm , Min – 70 X 120 mm
- Document Thickness: 0.06 – 0.15 mm
- Print Method: 0.06 – 0.15 mm
- Print Method: Thermal Printing
- Recording Paper Size: 216 mm X 15M, outer diameter=40mm
- Recording Width: 216 mm
- Resolution: Horizontal – 8 dots/mm; Vertical – Standard Mode – 3.85 lines/mm; Fine mode – 7.7 lines/mm
- Coding Scheme: MH
- Modem: V.29, V.27 ter with fall back function
- Modem Speed: 9600/7200/4800/2400 bps (automatically fall back)
- Power Supply: Single phase 22OV, model: 180-260V AC, 50/60Hz, Single phase
- Power Consumption: Standby: 6W ,Max: 90W
- Operating Environment: Temperature: 5-400 C (41-950F)
- Humidity: 45-85%
- Housing: It is housed in an elegant metal cabinet
- Power: 230VAC – Mains operated