Product name:	Product code:
PA (Public Address) System Trainer	Consumer0018

Description

PA (Public Address) System Trainer

Technical specification

- Output Tap for speaker matching : 4,8 &16 Ohms.
- Good Quality,reliable terminal/sockets are provided at appropriate places on panel for connections / observation of waveforms.
- Strongly supported by detailed Operating Instructions, giving details of Object, Theory, Design procedures, Report Suggestions and Book Reference
- Weight :16 Kg. (Approx.)

PA (Public Address) System Trainer

The P.A. System Trainer consists of :

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

- The complete circuit of public address amplifier is printed on single PCB.
- All part are soldered on PCB.
- Explanation, Observation, Alignment and adjustment of internal and external control possible due to single PCB.
- Easy identification of different parts is possible at a glance.
- Easy measurement of voltages and observation of waveforms at any point. Also typical voltages and waveforms are provided.
- A manual having practical detail is provided with the trainer.
- The whole circuit of public address amplifier is explained sectionwise in the manual.

Technical Specifications :

- Signal to noise ratio : 60 dB.
- Frequency response :100 Hz to 15000 Hz.
- Amplifier with two mic.inputs.
- One mic. & One Aux. inputs.
- Power supply : 220VAC 50 Hz.
- Power Output : 80 Watt RMS Max.
- Tone control : Bass, Treble.
- Audio Monitoring Indicators.