Product name:	Product code:
B.O.D. Incubator	ANL-BOD-0001



Description

B.O.D. Incubator

Technical specification

505x415x830	6.1 cu.ft.	171 ltrs.
565x565x865	10 cu.ft.	280 ltrs.
650x580x900	12 cu.ft.	336 ltrs.
700x650x900	15 cu.ft.	420 ltrs

Double wall construction.
Inner chamber made richly anodized aluminium or highly polished stainless steel sheet.
Supplied with two/three removable perforated shelves.
Exterior made out of thick mild steel sheet duly finished in white staying enamel/powder coated paint with mat finished colour combination.
Outer double wall door is provided with magnetic gasket and lock & key arrangement.
Inner door unbreakable acrylic transparent sheet for inspection of material in the chamber without disturbing the chamber temperature.
Optional:
Timer 0-24 hours day night cycle.
Co2 /air mixer nozzle is provided.
Internal illumination with 3 fluorescent tubes.
Microprocessor PID digital temp. Indicator-cum-controller.
Automatic Voltage stabilizer 3-5 KVA (recommended-must).

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Inner Chamber size in mm WxDxH	Capacity in Cu.ft	Capacity
405x405x405	2.4 cu.ft.	65 ltrs.
455x410x610	4 cu.ft.	112 ltrs.