Product name:	Product code:
Adsorption	NEECHL0243



Description

Adsorption

Technical specification

- max. head: 160m Heater
- max. power: 500W Measuring ranges
- flow rate: 0…60L/h
- temperature: 0…60°C
- pressure: 0…2,5bar 230V, 50Hz, 1 phase 230V, 60Hz, 1 phase 120V, 60Hz, 1 phase

UL/CSA optional

Dimensions and weight LxWxH: 1500x790x1900mm Weight: approx. 180kg

Installation & Basic operational training included

- o 2 adsorbers with activated carbon filling
- o adsorber with 8 sampling points
- o safety adsorber for closed water circuit
- o continuous process
- o metering pump for concentrated adsorbate solution
- o pump for circulating the treated water
- o water temperature control
- o digital temperature indication
- o flow rate adjustable
- o change of adsorbate concentration and contact time Technical data

NAUGRA®
Civil Laboratory Equipment Manufacturers and Suppliers India Civil Lab Exportrs India
Email us at: export@civilmechanicalindia.com

Adsorber and safety adsorber

- inside diameter: each 60mm
- height: each 600mm
- capacity: each 1700cm3 Tanks
- treated water: 45L
- adsorbate solution: 45L Circulation pump
- max. flow rate: 180L/h
- max. head: 10m Metering pump
- max. flow rate: 2,1L/h