

Product Name :
50 Hp Tractor

Product Code :
NUGEE0013



Description :

50 Hp Tractor

Technical Specification :

Diesel Engine (Yanmar or Perkins or Yamaha or Honda or Cummins or Mitsubishi or Hyundai), 4 WD: Engine HP (kw) - Gross 50.7 (37.3) \pm 2%, PTO HP (kw) 39.8 (29.3) \pm 2%, Rated Engine Speed 2800 rpm \pm 2%, Number of Cylinders 4, Displacement cu.in (cc) 135.2 (2216) \pm 2%, Air Cleaner Dual Dry,

Electrical System:

Alternator 12V, 65A;

Drivetrain:

Transmission Type Sync/Shuttle, Number of Speeds 16/F 16/R, Max Traveling Speed mph (km/h) above 20.7 (33.7) \pm 2%, Brakes Wet Disc, Steering Hydrostatic, Clutch dry single plate,

Hydraulic system:

Pump (type) Dual Gear Pump, Implement Pump Cap gpm (l/min) 8.8 (33.5) \pm 5%, Steering Pump Cap gpm 4.6 \pm 2%, Maximum Total Flow gpm 13.4 \pm 2%, Hitch Lift Capacity lb (kg) 2875 (1300) \pm 2%, 24 inches Behind Link Ends, lb (kg) 2105 (955) \pm 5%, Lift Control Type: Position/Draft, Joy Stick Valve: Standard, Number of Standard Remote Valves 2,

PTO:

Type Independent, Control Electric/Hydro, Mid (rpm) N/A, Rear (rpm) 540, 3 point Hlitch system category II,

Capacities:

fuel tank USGal (L) 17 (60) \pm 5%, cooling system US qt. (L) 9.0 (8.5) \pm 5%, crankcase (with filter) US qt. (L) 7.1 (6.7) \pm 5%, trans. & Hydr System US gal. (L) 9.2 (35) \pm 5%, fron axle qt. (L) 10.5 (10) \pm 5%,

Dimensions:

overall length in (mm) with 3P about 141.3 (3590) \pm 10%, overall width in (mm) about 62.6 (1591) \pm 5%; wheel base in (mm) about 76.2 (1935) \pm 10%, height to top of ROPS in (mm) 101.9 (2590) \pm 10%, Min. Ground Clearance, in (mm) 13.8 (350) \pm 5%, Min. Turning Radius, in (mm) with Brakes 131.9 (3352) \pm %, Min. Turning Radius, in (mm) w/o Brakes 150.4 (3820) \pm 5%.

Tires:

Front Tires 8.0 - 16, Rear Tires 13.6 - 24 \pm 2%. With foldable ROPS, Cab, front and rear wiper, head lamps, electric plug and brake hose for trailer, dual air filter, and hydrostatic power steering and combined meter.

Warranty:

12 months or 1000 hours. Supplier will provide parts and materials for maintenance and services as follows: engine oil, filter and air filter change: 250, 500, 750 and 1000 hours. Transmission oil: 500 and 950hours.

Civil Mechanical India

Website: www.civilmechanicalindia.com, **Email:** export@civilmechanicalindia.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, +91-0171-2601773