Product Name:

Diac Characteristics

Product Code:

EEN0022



Description:

Diac Characteristics

Technical Specification:

Diac Characteristics 01. To plot V-I Characteristics of a DIAC and study the following :

- 1. Breakover voltage, VBO.
- 2. Negative resistance region.
- 3. VBO symmetry and delta V

- 02. To study the applications of a DIAC as:
- 1. Saw tooth waveform generator.
- 2. Pulse train generator.

Features:

The board consists of following built-in parts:

- 1. 0-50V D.C. at 50mA, regulated Power Supply.
- 2. 45V A.C. at 50mA, unregulated Power Supply.
- 3. D.C. Voltmeter, 65mm rectangular dial to read 0-50V D.C.
- 4. D.C. Ammeter, 65mm rectangular dial with switch selectable ranges of 200mA and 50mA.
- 5. DIAC.
- 6. Potentiometer and adequate no. of other electronic components.
- 7. Mains ON/OFF switch, Fuse and Jewel light.
 - The unit is operative on 230V ±10% at 50Hz A.C. Mains.
 - Adequate no. of patch cords stackable from rear both ends 4mm spring loaded plug length ½ metre.
 - Good Quality, reliable terminal/sockets are provided at appropriate places on panel for connections / observation of waveforms.
 - Strongly supported by detailed Operating Instructions, giving details of Object, Theory, Design procedures, Report Suggestions and Book References.
 - Weight: 3 Kg. (Approx.)
 - Dimension: W 340 x H 110 x D 210

Other Apparatus Required:

Cathode Ray Oscilloscope 20MHz

Civil Mechanical India

Website: www.civilmechanicalindia.com, Email: export@civilmechanicalindia.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, Phone: +91-0171-2643080, +91-0171-2601773

3/3