

This unit has double walled chamber with interior made of Stainless Steel and Exterior is either made of Mild Steel finished.

Standard Fitting:-

S.S Enclosure, Motor, Controller PID, Power Cord, Tube Heater, Rubber Gasket, S.S Tray, Door Lock.

Features:-

Designed, fabricated to suit various applications in Laboratory/Hospitals.

Double walled chamber with interior made of Stainless Steel and Exterior is either made of Stainless Steel/Mild Steel powder coated.

Gap of inner & outer walled filled with sufficiently thick Glass wool insulation.

Long lasting S.S. tubular heater are mounted at bottom to give uniform heating.

Motorized blower for maintaining uniform temp. with in chamber, blowing in Air from bottom.

Microprocessor based Controller cum Indicator with pt. 100 sensor.

٦

Т

Optional – P.I.D. Controller with Printer Interface P.I.D. Controller with PC Interface.

Юарасіty Size (Inch)	
300.1r\$00pr800	
₲₲₵₶₨₱₲₡₥₡₡	
526 kt5608xp5000x	
820 kt6s0App602	
826 kt660Appp900	

3 000.tr2App 101500			

Civil Mechanical India

Website: www.civilmechanicalindia.com, Email: export@civilmechanicalindia.com Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, Phone: +91-0171-2643080, +91-0171-2601773