

Product Name :
Microprocessor Flame Photometer

Product Code :
ANL-FLM-0001



Description :

Microprocessor Flame Photometer

Technical Specification :

Microprocessor Based with Printer Interface

Auto Gas Cutoff

Auto Flame Failure Detection

Four Measurements in Single Aspiration

Setup Storage Facility

Sample Data Storage Facility

Curve Calibration Programmability Using Maximum of 5 Standards

Multiple Calibration Curve Saving Facility

Data Processing Through Curve Fitting Techniques, Least Square, Quadratic

Online Help Key

Direct Results in ppm and meq

Useful for Medical & Soil Testing

Microprocessor Flame Photometer comes with flame failure detection and auto gas cutoff facility.

In case of power failure, the gas cuts off automatically.

In case the flame goes off accidentally during work, the flame failure alarm sounds after few seconds

Microprocessor Flame Photometers are used for the determination of sodium, potassium, calcium and lithium.

They use the latest microcontroller technology and advanced engineering techniques so as to give enhanced and reproducibility.

They have soft touch membrane key for ease of operations.

The sample solution is aspirated through an atomiser.

Sample, Air and the fuel are mixed in the mixing chamber which is then sprayed as a very fine mist into the flame.

The color of the flame is changed depending upon the concentration of elements present.

Radiations from the flame pass through the sensing system and specific narrow band interference filter which permits only the characteristic radiation to pass to the photo-detector.

The output of the photo-detector is then processed by the microcontroller and the final results are displayed on the 20 x 4 line alphanumeric LCD with backlit.

In both models 5-Point calibration facility and non-linearity correction is provided through an automatic curve fitting software.

Facility has been provided for re-standardization with a single standard, thereby, eliminating the need of the multiple standards once a calibration has been performed.

Range 250 ppm

Upto 250 meq/l,
1:100 dil

K: 0 - 100

K: 0 - 100 ppm

1:100 dil

Upto 250 meq/l,

1:100 dil

Ca: 0 - 10

Ca: 0 - 100 ppm

Upto 250 meq/l,

1:100 dil

Li: 0 - 2

1:5 dil

Li: 0 - 100 ppm

Upto 250 meq/l,

1:100 dil

Sensitivity Na: 0.5 ppm, K: 0.5 ppm,
Li: 0.5 ppm, Ca: 15 ppm

Na & K supplied (Ca & Li are optional at extra
cost)

Resolution
0.1 ppm/meq

Repeatability
1% coefficient of variation

for 20 consecutive samples using 10 ppm Na set as maximum standard	
2% Feed Forward 3 ppm Na/K and 5 ppm Li are set as maximum standards	
Display alphanumeric LCD with backlit	
Average in Software	
EPON System oil free air	
Silicon photodiode	
Optical Point calibration with curve fitting software	
Adjustable with knobs	
Alarm Feature (Model - 1385)	

Gas Cutoff (Model - 1385)	
Ignition System	
Available type	
Provision for attachment of dot matrix printer or HP laserjet/ inkjet (non-windows) printers with centronics parallel interface	
PC-2206 (PC software at extra cost)	
Power	
200 W + 10% AC, 50 Hz	
Dimensions 210 mm (L x B x H) (Approx.)	
Weight (Approx.)	

Compressor Unit

Air Supply By Supply mini compressor unit with pressure regulator

Pressure Controlled by precision regulator

Power + 10% AC, 50 Hz

Dimensions 210 mm (L x B x H) (Approx.)

Civil Mechanical India

Website: www.civilmechanicalindia.com, **Email:** export@civilmechanicalindia.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, +91-0171-2601773