

Product Name :
Positive Displacement Pump Support Module

Product Code :
Chemical0004



Description :

Positive Displacement Pump Support Module

Technical Specification :

Positive Displacement Pump Support Module

Positive Displacement Pump Support Module

1. Operating Conditions

-
2. Operating environment: Laboratory
 3. Storage temperature range: -25°C to $+55^{\circ}\text{C}$ (when packed for transport)
 4. Operating temperature range: $+5^{\circ}\text{C}$ to $+40^{\circ}\text{C}$
 5. Operating relative humidity range: 80% at temperatures $< 31^{\circ}\text{C}$ decreasing linearly to 50% at 40°C

Technical Specifications

1. Nett dimensions and weight (assembled): 1540 mm x 1620 mm x 660 mm and 138 kg (with no oil in the reservoir)
2. Approximate packed volume and weight: 1.6 m³ and 250 kg (with oil)
3. Oil reservoir capacity: 30 litres
4. Oil type: Shell Morlina 10 or equivalent
5. Temperature measurement: K-type thermocouple and display

Civil Mechanical India

Website: www.civilmechanicalindia.com, **Email:** export@civilmechanicalindia.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, +91-0171-2601773